TPWLKI SERIES STAINLESS STEEL PALLET TRUCK SCALE



Stainless steel AISI 316 pallet truck scale Stainless steel AISI 304 indicator Stainless steel AISI 660 load cells

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Modem radio option box
- WI-FI interface
- Alibi memory with time-date
- Time-Date
- Versions with special capacities and/or divisions or high resolution (ask for price estimate)

Stainless steel pallet truck scales with built-in multirange electronic weighing, easy to use. Weight detection with four IP68 stainless steel load cells. Sturdy structure suitable for harsh work conditions. Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy +/- 0.1% of the maximum capacity.
- Fork dimensions 1180 x 550 x 80 mm. Weighs about 135 kg.
- Bearing structure entirely in extra thick STAINLESS steel AISI 316.
- Lifting pump in STAINLESS steel.
- Steering wheels and double loading rollers in nylon.
- 4 IP68 stainless steel AISI 660 shear beam load cells.
- IP65 stainless steel AISI 304 weight indicator, easy to clean and resistant to harsh and corrosive environments; large 25mm backlit LCD display, clearly visible also in poor lighting conditions, and waterproof keypad, with 17 numerical/functional keys.
- Calibration and Set-Up from keyboard or from PC.
- Power supply through built-in rechargeable battery.
- 80-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low battery warning.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control.
- Fitted with thermal printer in the TPWLKIP and TPWLKIPM versions.

MAIN FUNCTIONS

- Zeroing, Tare, Printing, numeric IDs
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Accumulation
- Formula weighing
- +/- Checkweighing
- Percentage weighing
- **Counting** (Max. resolution of 1.500.000 divisions)

Available versions				
Code	Max Capacity kg	Division kg	CE-M Division kg	
TPWLKI	500 / 1000 / 2000	0,2 / 0,5 / 1		
TPWLKIM M	1000 / 2000		0,5 / 1	
TPWLKIP	500 / 1000 / 2000	0 2 / 0,5 / 1		
TPWLKIPM M	1000 / 2000		0,5 / 1	

SWM	WeiMonitor PC program for monitoring and recording in real time all the weighs executed on the connected scale.	
DFCLK	Real time clock for printing/displaying of the date and time.	
ALMEM	Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight to PC/PLC. Real time clock	
	integrated for print of the date/time.	
WIFIT	WI-FI interface for wireless connection (through access point) to the company computer system.	

Accessories		
Code	е	Description
LNLE	ESS	60 rolls of Linerless thermal sticker paper, 57mm x 21m size, 49mm outer diameter, 12mm diameter central hole.
UKPL	LUG	Power adapter from Schuko to BS1363.
TEC	MAN	Printed technical manual (free, if downloaded from the web). NET PRICE.
UMA	N	Printed user manual (free, if downloaded from the web and available in the CD, fitted with the product). NET PRICE.