



TPWP

TPWP "PROFESSIONAL" SERIES PALLET TRUCK SCALE



Pallet truck scale supplied with new DFW series integrated weighing indicator. The new program allows the user to easily access to main software functions and weighing operations. TPWP's flexibility makes them indispensable in harsh working environments for anyone who needs to weigh accurately any type of product on a pallet. Manufactured, calibrated and adjusted in Italy by Dini Argeo, using certified sample masses. Available also CE-M APPROVED.

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- Maximum lifting capacity: 2500 kg.
- Accuracy: +/- 0.05% of the maximum capacity.
- Fork dimensions 1150 x 550 x 85 mm.
- Weighs about 125 kg.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- Standard fitted with +/-160° swivelling column head.
- Steering wheels and double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 load cells.
- Indicator with easy to clean ABS waterproof IP65 case enclosure built to withstand humid and dusty environments; large LCD display with 25 mm high contrast digits, which are clearly visible even in poor lighting conditions; 17-key numerical/functional membrane waterproof keyboard.
- Calibration and Set-Up configurable from keyboard or from PC with DINITOOLS.
- Standard supply with extractable rechargeable long lasting battery, with INSTAPLUG reversible quick coupling connector. Fitted with battery charge.
- 60-hour approximate operating time or three months with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low Battery Warning.
- Equipped with 230Vac 50 Hz battery charger.
- Bi-directional RS232/C port configurable for connection to printer.
- Bi-directional RS232/C serial output for radio modem, PC or portable terminal.
- IR input for managing the remote control.

## AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

DETAIL 1



Swivelling head +/-160°.

DETAIL 2



Closed Forks underside, for a higher protection against dirt.

### DETAIL 3



Extractable rechargeable battery.

### DETAIL 4



Battery with INSTAPLUG innovative quick coupling wireless system.

## VERSIONS

### Available versions

| Codice              | Max<br>(kg)       | d<br>(kg)     | <b>M</b><br>(kg) | d HR<br>(kg)*   |
|---------------------|-------------------|---------------|------------------|-----------------|
| TPWP25D-3           | 600 / 1500 / 2500 | 0,2 / 0,5 / 1 | --               | 0,1 / 0,2 / 0,5 |
| TPWP15DM-3 <b>M</b> | 600 / 1500        | --            | 0,2 / 0,5        | --              |
| TPWP25DM-3 <b>M</b> | 1500 / 2500       | --            | 0,5 / 1          | --              |

(\* ) The HR division is obtainable only with the relative EHR option.

*Please take note that the column and the handle-bar require assembly.*



MWS LTD

UNIT 6, MEER END - LE4 3EH - BIRSTALL - LEICESTER - UNITED KINGDOM

Tel. 08452602602

Fax. 0044-08452602612

E-mail [sales@mws.ltd.uk](mailto:sales@mws.ltd.uk)

Web [www.mws.ltd.uk](http://www.mws.ltd.uk)