

WWSERF

"WWSERF": 750 x 450mm WIRELESS WHEEL WEIGHING PADS



Wireless pads designed for creating wheel and axle vehicle weighing stations, avoiding the hassle of connecting cables between the pads and the indicator. Ideal for weighing larger vehicles (vans, trucks, tankers, trucks etc..); particularly accurate and sturdy, with attention to details.

The best solution for advanced industrial applications

FEATURES

- Pad dimensions:
 - weighing surface: 750 x 450 x 58 mm.total (with wheels): 805 x 561 x 58 mm.
- Weight approximately 28kg.
- Transit area: 603 x 450 mm.
- · Very handy.
- Sturdy structure, made in special aluminium, which guarantees lightness and makes these pads suitable also for harsh working conditions.
- · Stainless steel load cells.
- Overall IP68 protection degree.
- Sturdy built-in weight indicator, protected thanks to an IP68 hermetic box.
- Built-in radio module for weight transmission to a remote indicator or external device. Max. functioning distance: 50m.
- Integrated wheels for easy transport and positioning.
- Power supply: internal rechargeable battery (about 40 h battery life), kept in hermetic box, and charger included (to not use as power adaptor).
- Special vulcanised nonslip rubber applied under the pad, for good grip on all types of surfaces.
- The WWS pads are patented; the number is 1.342.302.
- Availables in legal for trade approved version.
- · Availables in high resolution version.

NOTES ON THE CE-M APPROVED VERSIONS

- The pads are for legal for trade use:
 - In the single-pad systems, not used to weigh vehicles.
 - In the wheel weighing systems in which the number of pads is equal to the number of vehicle wheels.
 - In the **axle weighing systems** composed of one or more multiples of WWS pads, except possible limitations of use for some European States.
- The CE-M legal for trade divisions indicated in the "version" table are available with ECEM option. ECEM option is needed for each legal for trade pad of the system.
- Legal for trade systems with more than one WWS, are fitted with the approval of the weight sum and related division:

Example for a 4 plaftorms system:

Single CE-M Pad: $\mathbf{Max} = 1500 \text{kg}$ and $\mathbf{e} = 0.5 \text{kg}$

CE-M SUM: Max=6000kg and e=2kg

WWS-R: Additional on/off ramps

• Integrated folding ramps, useful to facilitate the boarding and the alighting of vehicles with small diameter wheels or moved with the engine off.



In the example, an application with 2 WWS-R ramps.

AXLE WEIGHING SYSTEM INSTALLATION:



VERSIONS

Available versions						
	lxwxh	Max	d	M	d HR	Note
Codice	(mm)	(kg)	(kg)	(kg)	(kg)*	11010
WWSE2G4-6T-1	750x450x58	6000	2	2	0,2	Price for single platform
WWSE2G4-10T-1	750x450x58	10000	5	5	0,5	Price for single platform
WWSE2G4-15T-1	750x450x58	15000 (12500**)	5	5	0,5	Price for single platform

^(*) These divisions are obtainable only with the relative options

^(**) With ECEM legal for trade approval , Max = 12500kg



MWS LTD

UNIT 6, MEER END - LE4 3EH - BIRSTALL - LEICESTER

Tel. 08452602602 Fax. 0044-08452602612 E-mail sales@mws.ltd.uk Web www.mws.ltd.uk